

SUMMIT SERIES

SUPERIOR PERFORMANCE | LOWEST COST | EXTREME RELIABILITY | CONTROLS OPTIONS

The Vega Light Control Systems SUMMIT Series offers revolutionary performance and features with the Patented D4A in a prismatic decorative luminaire system engineered to last.

Superior light performance, reduced glare, ultra long life components including 36 kV surge suppression standard, and more, create a system of unsurpassed value and performance. Plus, it's available with a broad range of controls and features including Adaptive Light Control.



SUMMIT SERIES

BEST IN CLASS PERFORMANCE

- Trouble free, Proven system
- Double or triple light coverage and life of most LED systems
- Uncompromising construction and materials
- Up to 160 Lumens Per Watt
- Reduced uplight glare by up to 60%
- 36 kV of surge suppression standard across all three lines
- Superior thermal design (no fans or thermal 'Band-aids')
- DLC Listing & UL Listed light source only *
- Top quality industry proven prismatic Acrylic, and Polycarbonate Globes for performance and color stability

OPTIONAL FEATURES

- Built in Controls - Bluetooth remote control using **VEGA Link IQ2 app**. Control light dimming, back light dimming, and front light dimming independently of each other.
- BUG Rating modification – independently modify Backlight, and Glare

SOON TO BE RELEASED

- RGB - High output colored light array that can render many colors or simply use preset colors for special events.
- Built in Mesh Networking – VEGA Link Mesh Control (modify one unit settings and 'sync' all others), lock individuals where needed, report diagnostics, faults, GPS location, and more.



RATED LIFE

100,000+ Hrs Rated System Life
80% Lumen Maintenance at 100,000 Hrs

TESTING

IESNA LM-80
InSitu Thermal
Energy Star TM-21
Surge & Transient Tested
100% Production Test & Inspect

LISTING

IP65 Wet Location Rated
Certification to UL 1598C, UL 8750, 1993
CSA C22.2 No.250.1 (Light Source only)
Complies with IEEE C62.41

SHIPPING INFORMATION

Ships from USA Mfg Plant
ISO 9001 US Facility

ELECTRICAL

36 kV Surge Suppression
Power Factor Correction >90%
<10% Total Harmonic Distortion
-40C to +50C Ambient Operating Temp
Universal 120-277 VAC, 480 VAC Option
Thermal Overload Protected
Electrical Short / Overload Protected




SUPPORT@VEGALIGHTCONTROL.COM
616.259.0700
VEGALIGHTCONTROL.COM

VEGA Link IQ D4A

The easiest way to maximize the benefits and savings of VEGA control products with a simple to use smart phone interface!



Available on:



Google Play and the Google Play logo are trademarks of Google LLC.
Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries and regions.
App Store is a service mark of Apple Inc.

